This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



37,275






FIG. 2

Demonstration of Stable Seal in Many Thermal Cycles





FIG. 3






FIG. 4

The Relationship Between the Increase in Pressure has on the Oxyen Flux




FIG. 5

La0.2Sr0.8Fe0.8Cr0.2O3-x Tube w/1mm Wall, He Sweep@2L/m, Air @4L/m, 975C




FIG. 6





FIG. 7






FIG. 8

Oxygen Utilization in Exit Air Stream at Ambient Pressure Fuel Stream Inlet: 0.2L/minH2, 1.0L/minCH4, 2.5L/minSteam at 1000C at 390 psid

